

Inspirations® TOUCHLESS

Filtration Cooler



New for 2021

All new TRUE TOUCHLESS Filtration water dispensers.

Be the *FIRST* in your market to offer a TRUE TOUCHLESS water cooler solution to the COVID-19 pandemic

Available Now



Features

- Sensor activated dispense
- Two sensors for hot water dispensing for safety
- **True Touchless** dispense requiring only one hand to operate and fill your container for both hot and cold water
- 2.0L / .53G stainless steel hot tank with all SS fittings between hot and cold tanks
- 3.8L / 1G polished stainless steel cold tank with laser welded joints and seams
- A new “D” shaped copper evaporator tubing means one side of the tubing is flat... creating more contact and more surface area with the cold tank which improves cold water performance.
- Evaporator copper tubing thickness is increased by 33%, providing longer life and resistance to “pin” hole refrigerant leaks.
- Dispense 4 inches higher for ease of dispense
- Upgraded internal supports to increase durability and reduces shipping and handling issues
- No external base plate
- Larger rear cabinet opening for easier chassis removal
- Available in black and white
- eTL listed
- Dual mechanical float

Inspirations[®] **TOUCHLESS** Filtration Cooler

Power

Voltage	115, 220, 110
Frequency (Hz)	50/60
Power Consumption	4.89A / 554W / 115V
Cold Power Consumption	1.44A / 118W 115V
Hot Power Consumption	3.87A / 449W / 115V
ES (kWh/24 hrs.)	0.86
% lower than ES Standard	1%

Hot Water System

Avg. Hot Water Temp at Nozzle @ 77°F Ambient (Cut-in / Cut-out Temp)	167°F +/- 9°F / 187°F +/- 4°F
Hot Water ARI Rating	45, 6 oz. > 165°F +/- 10%
Hot Thermometer / Heat Limiter	203°F +/- 5.5°F
Hot Thermostat / Thermistor Cycle	167°F +/- 9°F / 187°F +/- 4°F
Hot Water Flow Rate	0.67 - 0.73 oz./sec
Hot Tank Size (L)	2.0L
Heat Band Wattage	450W

Cold Water System

Avg. Cold Water Temp at Nozzle @ 75°F Ambient (Cut-in / Cut-out Temp)	45.87°F / 42.2°F
Cold Water ARI Rating	45, 5 oz. > 50°F +/- 10%
Cold Thermostat Set Point	45°F + 3°F/-8°F
Cold Water Flow Rate	1.4 oz./sec
Cold Tank Size / Usable Volume / Below Baffle Cold Water (Liter : Gallon)	3.78 / 2.08 / 1.51 : 1 / 0.55 / 0.4

Weights and Measurements

Net Weight (H&C / C&C Lbs.)	31 / 27
Gross Weight (H&C / C&C Lbs.)	33 / 30
Max Distance from Drip Tray to Faucet (Inch : mm)	7.8 : 199
Faucet / Dispense Height (Inch : mm)	28.75 : 730.25
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	12.4x13.78x42.91 / 13x13.9x43.9
Container Load (20')	224
Container Load (40')	462
Container Load (40' HC)	462
Container Load (45' HC)	518
Certifications	ETL Listed
Models (POU: H&C : C&C)	IB215r-TL, IW215r-TL : IB115r-TL, IW115r-TL

Warranty:

3 years: Sealed refrigeration system
 2 years: Parts (electrical to include cold controls, relay overloads and PCB's)

phone: (909) 629-7301
 Canada: (905) 302-7896
 email: info@aquabeve.com
 Web: www.aquabeve.com

